

200mA, 30V Schottky Barrier Diode

FEATURES

- Fast switching speed
- Surface mound device type
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Adapters
- For switching power supply
- Inverter

MECHANICAL DATA

- Case: SOT-23
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1A whisker test
- Weight: 8.00mg (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	200	mA
V_{RRM}	30	V
I_{FSM}	600	mA
V_F at $I_F = 100\text{mA}$	1	V
$T_{J\text{MAX}}$	125	°C
Package	SOT-23	



SOT-23

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER	SYMBOL	BAT54	BAT54A	BAT54C	BAT54S	UNIT
Marking code on the device		KL1	KL2	KL3	KL4	
Power dissipation	P_D	200				mW
Repetitive peak reverse voltage	V_{RRM}	30				V
Repetitive peak forward current ($t_p \leq 1\text{s}; \delta \leq 0.5$)	I_{FRM}	300				mA
Forward current	I_F	200				mA
Non-Repetitive peak forward surge current @ $t < 1.0\text{s}$	I_{FSM}	600				mA
Junction temperature range	T_J	-55 to +125				°C
Storage temperature range	T_{STG}	-55 to +125				°C

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	TYP	UNIT
Junction-to-ambient thermal resistance	$R_{\theta JA}$	500	°C/W

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)					
PARAMETER	CONDITIONS	SYMBOL	MIN	MAX	UNIT
Forward voltage per diode ⁽¹⁾	$I_F = 0.1\text{mA}, T_J = 25^\circ\text{C}$	V_F	-	0.24	V
	$I_F = 1\text{mA}, T_J = 25^\circ\text{C}$		-	0.32	V
	$I_F = 10\text{mA}, T_J = 25^\circ\text{C}$		-	0.40	V
	$I_F = 30\text{mA}, T_J = 25^\circ\text{C}$		-	0.50	V
	$I_F = 100\text{mA}, T_J = 25^\circ\text{C}$		-	1.00	V
Reverse voltage	$I_R = 100\ \mu\text{A}, T_J = 25^\circ\text{C}$	V_R	30	-	V
Reverse current @ rated V_R per diode ⁽²⁾	$V_R = 25\ \text{V}, T_J = 25^\circ\text{C}$	I_R	-	2	μA
Junction capacitance	$f = 1\text{MHz}, V_R = 1\text{V}$	C_J	-	10	pF
Reverse recovery time	$I_F = I_R = 10\text{mA},$ $R_L = 100\Omega, I_{rr} = 1\text{mA}$	t_{rr}	-	5	ns

Notes:

1. Pulse test with PW = 0.3ms
2. Pulse test with PW = 30ms

ORDERING INFORMATION		
ORDERING CODE ⁽¹⁾⁽²⁾	PACKAGE	PACKING
BAT5x RF	SOT-23	3K / 7" Reel
BAT5x RFG	SOT-23	3K / 7" Reel

Notes:

1. "x" defines part no. from "4" to "4S"
2. "G" means green compound (halogen-free)

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Typical Forward Characteristics




Fig.2 Typical Reverse Characteristics




Fig.3 Admissible Power Dissipation Curve






Fig.4 Typical Junction Capacitance




PACKAGE OUTLINE DIMENSION

SOT-23




DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	0.89	1.12	0.035	0.044
b	0.30	0.50	0.012	0.020
c	0.08	0.20	0.003	0.008
D	2.80	3.04	0.110	0.120
E	2.10	2.64	0.083	0.104
E1	1.20	1.40	0.047	0.055
e	1.90 BSC		0.075 BSC	
L1	0.54 REF.		0.021 REF.	

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	1.00	0.039
B	0.85	0.033
C	2.10	0.083
D	3.10	0.122
E	0.98	0.039

PIN CONFIGURATION



Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[BAT54](#) [BAT54A](#) [BAT54C](#) [BAT54S](#) [BAT54S RFG](#) [BAT54 RF](#) [BAT54C RFG](#) [BAT54A RF](#) [BAT54S RF](#) [BAT54 RFG](#) [BAT54A RFG](#)